



A TECHWELL EVENT

## **W15**

People & Teams

Wednesday, October 17th, 2018 3:00 PM

# **Testing at 43,000 Feet: Reporting Risk That Matters**

Presented by:

**Alexandre Bauduin**

Brought to you by:




350 Corporate Way, Suite 400, Orange Park, FL 32073  
888-268-8770 · 904-278-0524 - [info@techwell.com](mailto:info@techwell.com) - <http://www.starwest.techwell.com/>

# Alexandre Bauduin


Alexandre Bauduin is a 51 year old world traveler. He worked in consulting firms gaining experience in several fields (medical, manufacturing, aerospace, pay TV, data warehouse-to name a few) in different countries (Switzerland, France, Spain, Canada, etc.) His career started in the space industry where he discovered his passion for aerospace, working on both military and civilian projects. He was sometimes steered away from aerospace but his passion pushed him to become an airline pilot, as a way to really understand how those instruments he programmed and integrated were operating in a cockpit. One of his last challenges was to organize flight simulator testing into a lean manufacturing environment. He works with milling machines, draftsmanship, accounting and finance, software development, electronic design and industrial robots, and it is always fun for him to use an oscilloscope, an ARINC bus analyzer, and step into assembly language or stall a Boeing 777!







## Short intro



## Topics

- what is simulated and how?
- what to test, evidences?
- what to report: Pass fail ratio! Or not.
- Testing examples and reporting



## what is simulated

Might be easy to note what is not simulated!

- Ocean tide
- Cloud temperature
- Sound of ULD loading
- Physical air pressure
- Earth curvature...

All not relevant for training ignored.



## How is it simulated ?



200 deg x 40 deg FOV  
Cockpit replica  
Cockpit panels  
Motion 6DOF platform  
controls with force feedback  
(450 lbs on 777)  
"In house" or OEM parts





## How is it simulated ?


Module for each "system" (Fuel, electrics, LG..)

```
Constant TimeUp = 20;  
Init();  
Timing = 0;  
while (true){  
    wait_For_Go();  
    //Landing gear selector  
    if (i32_LdgSel== UP) && (Timing < TimeUp) {  
        Retract_a_bit_LandingGear();  
        Timing++  
    }  
    rest of the code...  
}
```

Nasa

## How is it simulated ?

Ground Proximity Warning system: OEM for aircraft



## How to test ?

### Regulation

ICAO: Main regulator

Each country has some more specific (ex. FAA Part 60)

Specify what, how, who, when around the simulator

It is a law. Do not mess with it! Traceability, rigorous.

### Electronic Code of Federal Regulations

e-CFR data is current as of **August 23, 2018**

[Title 14](#) → [Chapter I](#) → [Subchapter D](#) → [Part 60](#)

[Browse Previous](#) | [Browse Next](#)

Title 14: Aeronautics and Space

**PART 60—FLIGHT SIMULATION TRAINING DEVICE INITIAL AND CONTINUING QUALIFICATION AND USE**



ICAO

UNITING AVIATION

## Biggest fear?

Major risk around « Negative training »

Teaching something incorrect to pilots

Pilot build « truth » based on what seen in training.





## Biggest fear?

To70 (Dutch consulting company) estimated that the fatal accident rate for large commercial passenger flights is 0.06 per million flights, or one fatal accident for every 16 million flights.

## How to test ?

Build the simulator and then send V&V

Authorities requirements = follow the list

TESTS	TOLERANCE	FLIGHT CONDITIONS	FSTD LEVEL										COMMENTS	
			FFS				FTD		FNPT			BITD		
			A	B	C	D	Init	Rec	I	II	MCC			
(5) Autopilot landing (if applicable).	± 1.5 m (5 ft) flare height. ± 0.5 s or ± 10%T <sub>f</sub> . ± 0.7 m/s (140 ft/min) R/D at touchdown. ± 3 m (10 ft) lateral deviation during rollout.	Landing		✓	✓	✓								If autopilot provides rollout guidance, record lateral deviation from touchdown to a 50% decrease in main landing gear touchdown speed. Time of autopilot flare mode engage and main gear touchdown should be noted. This test is <u>not</u> a substitute for the ground effects test requirement. T <sub>f</sub> = Duration of flare.

Used for performance of the airplane, flight control forces, sound quality

## How to test ?

### Data injection from real flight into simulation

All automated  
150-200 cases  
Need some tuning (mechanical parts)  
Yield 2500 pages of tests results

Required to explain any deviation






Figure 2e4-1  
Example of Simulator Test Results for Engine Inoperative Landing 2E-15

## How to test ?

### System: Perform manual checks

Note: Skip tests as required for LLD	Pass	Fail
Reposition to take off.		
Check		
Gear indication DOWN green	-	-
Landing gear doors closed	-	-
Try to raise landing gear		
Check lock solenoid prevent landing gear selector <b>MOV.</b>	-	-
Check gear indication: no change	-	-
Perform normal take off do not retract gear.		
Increase speed to 250 <b>Kts.</b>		
Check		
Landing gear vibration increased with speed	-	-
Landing gear sound increased with speed	-	-
Move landing gear selector UP		
Check		
DOWN green is replaced by hatched white indication	-	-
Gear doors sound audible	-	-
Gear up bump motion present	-	-
After 17 seconds UP green appears	-	-
Hatched white indication disappears	-	-
Open alternate gear selector cap		
Hold down switch for 7 seconds		
Check .....		





# what to report ?

**Pass or fail?**

Product	Pass	Fail
Prod1	0.03	Pass
Prod2	0.01	Pass
Prod3	0.10	Fail

**HOW-TO MAKE A PASS FAIL CHART**

**MAM1010F NSC Maths vs NBT Maths Pass/Fail (at 50%) ratio**

Product	Pass	Fail
Prod1	0.03	Pass
Prod2	0.01	Pass
Prod3	0.10	Fail

17-20 thousand ticks  
One month of checking  
Pass fail per system  
1000 issues

# what to report ?



-What is the status?  
-All pumps running!

challenge the question



## what to report ?

Ensure that every story is covered by a test case?

Given weapon system armed  
When pilot presses release button  
Then bomb is released

Exit criteria met. And?



## what to report ?

Test are 100 % passing so all good.

Exploded after take off:  
Overflow, exception not trapped  
Induced by:  
5 times more acceleration vs Ariane 4

More on Wiki

**Context : Data and test content designed in point in time**





## what to report ?

Testing boundaries in aviation is important:

```
Float outsideAirTemperature (float staticTemperature...)
```

```
{
```

```
    Some magic calculations;
```


```
    Return result;
```

```
}
```

OAT in aviation : -73c / 55c  
-100 / + 100 to be safe.

## what to report ?

Tools and CLERC (C Level Executive Ready Charts)



Jira, Xunit, Static code metrics, branch coverage, Jenkins builds...

You are the expert: Numbers are right!?



## what to report ?

If defective...




	Pass	Fail
Note: Skip tests as required for LLD		
Reposition to take off.		
Check		
Gear indication DOWN green	-	X
Landing gear doors closed	-	X
Try to raise landing gear		
Check lock solenoid prevent landing gear selector <i>mv</i> t	-	X
Check gear indication: no change	-	X
Perform normal take off do not retract gear.		
Increase speed to 250 Kts.		
Check		
Landing gear vibration increased with speed	-	X
Landing gear sound increased with speed	-	X
Move landing gear selector UP		
Check		
DOWN green is replaced by hatched white indication	-	X
Gear doors sound audible	-	X
Gear up bump motion present	-	X
After 17 seconds UP green appears	-	X
Hatched white indication disappears	-	X
Open alternate gear selector cap		
Hold down switch for 7 seconds		
Check .....		

Could you help me get that fixed?

## what to report ?

Ground Proximity Warning System: OEM for aircraft



Certified to be installed in real plane  
Firmware certified by aviation

Equipped with « self test »

Third party: knowing it helps estimating risks



## what to report ?

Automatic « testing » framework to the rescue

2202 test « cases » automated  
8 modules ENTIRELY automated

How many phone numbers you know now?

Expertise in automation  $\leftrightarrow$  expertise in product

## what to report ?

could you verify that 5000 cars per hour EAST WEST is OK?



Testing does not always requires code!



## what to report ?

Keep test procedure "light", too many maintenance!!

TABLE OF FUNCTIONS AND SUBJECTIVE TESTS	FFS			
	A	B	C	D
(11) Tyre failure dynamics			✓	✓
(a) Dependent on aeroplane type, a single tyre failure may not necessarily be noticed by the pilot and therefore there should not be any special motion effect. There may possibly be some sound and/or vibration associated with the actual tyre losing pressure. With a multiple tyre failure selected on the same side the pilot may notice some yawing which should require the use of the rudder to maintain control of the aeroplane				



Pass      Fail

Reposition to take off  
 Increase speed to 80kts  
 Blow tire 11 on left main gear  
 Check  
 Effects are representative

—      —

## what to report ?

Mathematic model for "contaminants" deposit on RWY

Float Temperature (float dewpoint, RelHum)

```
{ ...
  Return x;
}
```

What occurs around freezing point?

Informal chit chat are worth it!





## what to report ?

we found 987 issues in the last version

Issue to fix = \$\$\$

32% contractual terms unclear  
17% fatal error (exception)

Oxford Comma Dispute Is Settled as Maine Drivers Get \$5 Million ...  
<https://www.nytimes.com/2018/02/09/.../oxford-comma-maine.htm...> - Traduire cette page  
9 févr. 2018 - And state lawmakers have dispensed with commas altogether in the ... of Appeals for the First Circuit ruled that the missing comma created ...

Being part of the problem or the solution

## what to report ?

Login feature has been tested!

What is understood? What do YOU mean?

so I can sell to Spain, Switzerland? ç öëëê

## Conclusion

Dash board and numbers are very easy to build

Not everybody is expert in your domain

Dashboard or a face to face discussion?

Reporting or learning?

## Questions and answers





Thank you, safe trip home!



[Alexandre.bauduin@houseoftest.ch](mailto:Alexandre.bauduin@houseoftest.ch)

Twit: @B777Alex